

LANDA®

Since 1969

Industrial Pressure Washers
...Built Right to Do the Job Right

SLX-SLT

The Only Portable Hot Water Pressure Washer that Delivers 200°F Cleaning at up to 9.5 GPM

- Dual-Gun Ready
- Powered by Gasoline or Diesel; Diesel-Heated
- Belt-Drive Landa Pump with 7-Year Warranty
- 3/4" Schedule 80 Coil



◀ Pre-plumbed with **3-Way Valve** to bypass float tank when drawing water directly from an auxiliary tank.

■ Extra-large **Heating Coil** made of cold-rolled, 3/4" Schedule 80 steel pipe with 5-year warranty; features **Stainless Steel Top Wrap**; unique lift-out design for easy and quick **Coil Access**.

■ Rugged 2" x 4" x 1/8" thick box steel frame, with compact footprint, shields key components; further protected by weather-resistant **Epoxy Powder Coat** finish; **Power Platform** is vibration isolated to minimize frame stress.

■ Water-resistant, metal **Control Panel** has adjustable thermostat, combination hour meter and tachometer, volt meter, burner switch and tri-lingual operating instructions for added safety.

■ Industrial-duty tri-plunger **Landa Pump** designed to run at low RPM for long life, 7-year warranty, with single-rail true-track **Pulley Adjustment**.

■ **Illustrated Warning Labels** universally understandable for liability protection.

■ 30-gallon diesel and 16-gallon gasoline **Fuel Tanks** (15-gallon diesel and 10-gallon gasoline on SLT) provide hours of uninterrupted operation; with elevated fuel lines to avoid suctioning of settled debris.

■ 50 ft. of double-wire braid **High Pressure Hose** rated for up to 6,000 PSI and featuring a 24-inch safety hose guard for operator burst protection.

■ High-efficiency **Burner**, with dual rings for "dialing in" air flow, has a **Fuel-Water Separator** for fuel pump protection.

■ **Many Safety Features**, including a rupture disk, thermal pump protector, flow switch, unloader valve, and safety lock on the trigger gun.

■ **Corrosion-resistant Float Tank** has stainless steel inlet filter and 3/4" float valve with anti-siphon backflow protection; also allows for introduction of detergents in high-pressure mode.

■ Insulated, fatigue-free **Trigger Gun**, with swivel crimp fitting for a tangle-free hose. Stainless steel, dual-lance **Variable Pressure Wand** features an ergonomic design and easy adjusting of the water pressure while cleaning.

■ Efficient **2,000-Watt Generator** produces reliable power for burner.



SLX

www.landa.com

LANDA®

Industrial Pressure Washers
...Built Right to Do the Job Right

Since 1969

SLX-SLT

The Only Portable Hot Water Pressure Washer
that Delivers 200°F Cleaning at up to 9.5 GPM

- Dual-Gun Ready
- Powered by Gasoline or Diesel; Diesel-Heated
- Belt-Drive Landa Pump with 7-Year Warranty
- 3/4" Schedule 80 Coil

WHY CHOOSE LANDA'S SLX or SLT

When it comes to heavy-duty grease or grime, most high-volume, hot water pressure washers fall short with their 150°F water. Landa's SLX, and smaller SLT, are the first power washers ever designed to deliver a high-volume flow at 200°F, hot enough to melt the toughest of oily messes. The SLX delivers enough hot water flow—up to 9.5 GPM—that you can operate two spray guns at the same time! Other benefits include:

QUALITY: Packed with Landa quality throughout, the SLX and SLT feature a top-of-the-line, belt-drive Landa Pump with 7-year warranty and low RPM for extended life, as well as a giant Schedule 80 heating coil, made of up to 300 ft. of 3/4-inch steel pipe with 5-year warranty.

DURABILITY: Extraordinarily rugged frame is made of 2-by-4-inch box steel with an all-metal power platform cushioned by 10 vibration isolators to minimize frame stress.

EFFICIENT: The SLX-SLT is heated by a high-efficiency Beckett burner with dual rings for dial-in air flow. The 3/4" heating coil is amazingly efficient due to its unique "breathing" design so it heats quieter while promoting optimum heat exchange.

FUNCTIONAL: The SLX-SLT has a remarkably compact footprint, is certified to UL-1776 safety standards, is pre-plumbed for drawing water from an auxiliary tank, has six forklift guides for portability and the control panel is ideally positioned for curb access when the unit is mounted on a trailer or truck bed.



SLT

SLX and SLT Specifications

Model No.	GPM	PSI	Engine	CCs	Engine Fuel	Gas Tank	Diesel Tank	Pump RPM	BTU's	L x W x H	SHIP WT.
SLX10-25324E	9.5	2,500	Honda GX660	688	Gasoline	16	30	1,560	887,000	65" x 36" x 58"	2,020 lbs.
SLX10-25824E	9.5	2,500	Kohler KDW1003	1028	Diesel	N/A	40	1,470	887,000	65" x 36" x 58"	2,160 lbs.
SLT6-32324E	5.9	3,200	Honda GX630	688	Gasoline	10	15	1,570	550,000	55" x 32" x 51"	1,245 lbs.
SLT8-30324E	7.8	3,000	Honda GX660	688	Gasoline	10	15	1,470	728,000	55" x 32" x 51"	1,230 lbs.
SLT6-32824E	5.9	3,200	Kohler KDW1003	1028	Diesel	N/A	26	1,470	588,000	62" x 32" x 53.5"	1,785 lbs.
SLT8-30824E	7.8	3,000	Kohler KDW1003	1028	Diesel	N/A	26	1,560	728,000	62" x 32" x 53.5"	1,851 lbs.

E=Electric Start

Note: LANDA is constantly improving and updating its products. Consequently, pictures, features, and specifications in this brochure may differ slightly from current models. Flow rates and pressure ratings may vary due to variances allowed by manufacturers of our machine components. LANDA product performance is certified by the Cleaning Equipment Trade Association (CETA) to be within 5% of listed specifications.

LANDA®

Distributed by:



Power Wash Detergents:
Landa has an extensive line of detergents formulated specifically for use with hot water pressure washers such as the SLX and SLT

www.landa.com