



# HOT WATER PRESSURE WASHER

## OIL / DIESEL FIRED



**Adjustable thermostat**  
up to 200°F with LED rocker switch and hour/tach meter

**American made**  
heavy duty 7000 PSI rupture disk

Heavy-duty **roll-cage powder coated 1.5" OD** steel tube frame, with centre balanced lift hook (above industry standards)

**Honda GX390** electric start w/ 18amp charge

triplex direct-drive general pump carries a **5-year warranty**

**Adjustable** pressure relief valve

**12" oil drain hose** for ease of maintenance

**7-gallon, removable, rust-proof polyethylene fuel tank** with fuel gauge in cap

**Brake assembly**

**Marine sealed battery** box with 55 AH AGM deep cycle battery

**3/4" HD Threaded** mount axle

**360° Hose reel** swivel bracket

### HEATING COIL

1/2" Heavy-duty schedule 80 American made Carbon Steel Cold-rolled pipe, no weak points from heating to make bends

5500PSI Rated, "Full Sized" 96' length for maximum heat rise and proper heat production

**Stainless-steel coil skin** provides extra durability and resists corrosion

**12v DC Oil-fired Beckett burner** with low voltage inhibitor, prevents burner from starting up if battery voltage is dropped

**Mounting bracket** for truck mounting

**12" heavy-duty flat free tires**

## FEATURES

- Gun/wand assembly with insulated grip and quick connects
- 50' high pressure hose w/quick connects
- 20% chemical injector assembly w/quick connects
- 4 color-coded QC spray nozzles
- 1 color-coded QC chemical nozzle



POWERED by **HONDA**



### DIRECT DRIVE

MODEL	GPM	PSI	CC's	ENGINE	BTU/HR	PUMP MODEL	DRIVE	BURNER FUEL CONS.	UNIT DIMENSIONS	SHIPPING DIMENSIONS	SHIP WT (lbs)
HW4013HG	4	4000	389	HONDA GX390	330,000	GENERAL PUMP EZ4040	DIRECT	2.21 GPH	47"L x 31"W x 50"H	52"L x 36"W x 55"H	530